



DRIVEN BY POSSIBILITY™

# Flotec

## MULTI MASTER™ GMV™ MEGAFLEX™



## ONE HOSE. FOUR USES. ULTIMATE FLEXIBILITY.



One hose engineered for four industrial applications: fuel, hydraulic return, coolant, and water, Gates Multi Master™ GMV™ MegaFlex™ delivers superior performance and ultimate flexibility.

We believe operating challenges are made to be overcome. That's why thousands of industrial facilities, global operations, and OE manufacturers around the world choose Gates hose and hydraulic systems to power their most demanding fluid power applications.

**MULTI-USE HOSE  
WITH SUPERIOR  
PERFORMANCE.**

### FEATURES + BENEFITS

One multi-use hose that meets SAE 100R4, J30R5, J20R5\* (\*except tube dimensions)

Consolidate inventory and meet global requirements

Industry-leading flexibility

Solves complex routings through tight spaces using less hose

Easy installation with 1:1 bend radius

Time saving and kink free

Light weight and ergonomic

Easy handling with lower risk of strain

ARPM Class A Tube

Provides maximum oil resistance

Sizes range from 3/4" to 6" and working pressures 150 to 350psi

Superior performance for multiple applications

MSHA approved cover

Flame resistant for critical and mining applications

# MULTI MASTER™ GMV™ MEGAFLEX™ PRODUCT SPECIFICATIONS

<b>TUBE</b>	Black, nitrile, oil resistant, ARPM Class A tube. SAE J20 Class B.
<b>REINFORCEMENT</b>	Synthetic, high tensile textile with steel wire helix.
<b>COVER</b>	Black, chloroprene, corrugated rubber. Meets MSHA flame resistance. SAE J20 Class C.
<b>MAX. WORKING PRESSURE</b>	150psi to 350psi, 10.3 to 24.1 bar, 1 MPa to 2.4 MPa.
<b>TEMPERATURE RANGE</b>	-40°F to +275°F (-40°C to +135°C) except for fuel and coolant applications.
<b>COUPLINGS</b>	GL (all sizes), G (3/4", 1" and 1 1/4"), GSP (1 1/2" and 2"). Clamps over stem/beaded nipple for low pressure applications.

## INDUSTRIES

Construction  
Oil + Gas  
Agriculture  
Mining

## APPLICATIONS

Hydraulic Return + Suction  
Petroleum Transfer  
Coolant Applications  
Water Suction + Discharge

**OUR GLOBAL FOOTPRINT  
HELPS YOU MOVE FORWARD.**

ID (IN)	ID (MM)	OD (IN)	OD (MM)	WP (PSI)	WP (MPa)	DESIGN FACTOR	MIN. BEND RADIUS (IN)	MIN. BEND RADIUS (MM)	WEIGHT (LBS/FT)	WEIGHT (KG/M)
3/4	19.1	1.20	30.5	350	2.4	4:1	0.8	20.3	0.4	0.6
1	25.4	1.41	35.8	300	2.1	4:1	1.0	25.4	0.5	0.7
1 1/4	31.8	1.66	42.2	250	1.7	4:1	1.3	33.0	0.6	0.9
1 1/2	38.1	1.90	48.3	160	1.1	4:1	1.5	38.1	0.7	1.1
2	50.8	2.39	60.7	150	1.0	4:1	2.0	50.8	0.9	1.3
2 1/2	63.5	2.94	74.7	150	1.0	4:1	2.5	63.5	1.2	1.8
3	76.2	3.44	87.4	150	1.0	4:1	3.0	76.2	1.5	2.2
4	101.6	4.48	113.8	150	1.0	4:1	4.0	101.6	2.3	3.4
6	152.4	6.55	166.4	150	1.0	4:1	6.0	152.4	4.0	6.0